

Needle roller bearing BRI264120-UU-IKO - BRI264120-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bri264120-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | |
|----------------------------|-----------------------|---------------|---------------------|------------------------------|-----------------------|-----------------------|---------------|
| | With two seals | With one seal | | d | D | C | B |
| 41.275 (1 13/16) | BRI 264120 UU | | 386 | 41.275 (1 13/16) | 65.088 (2 3/8) | 31.750 (1 1/4) | 32.000 |

| F_w | Standard mounting dimensions (mm) | | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ^(*) rpm | Assembled inner ring LRBZ 263220 B |
|--------------------|-----------------------------------|-----------|-----------------------------|-------------------------------------|--|--|---------------------------------------|
| | Min. | Max. | Max. as max. ^(*) | | | | |
| 50.800 (2) | 48 | 49 | 57.8 | 51 000 | 89 400 | 4 000 | |

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952382692 |
| Inside diameter | 41.275 mm |
| Outside diameter | 65.088 mm |
| Thickness | 31.75 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE