

Needle roller bearing BRI325228-U-IKO - BRI325228-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bri325228-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
50.800 (2)		BRI 325228 U	889	50.800 (2)	82.550 (3 $\frac{1}{4}$)	44.450 (1 $\frac{3}{4}$)	44.700
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 324028 B
	Min.	Max.	as max. ^(*)				
63.500 (2 $\frac{1}{2}$)	58	61	74.3	94 600	174 000	3 000	

Notes: (*) Minimum allowable value of diameter dimension r.
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382722
Inside diameter	50.8 mm
Outside diameter	82.55 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE