


Needle roller bearing BRI325228-UU-IKO - BRI325228-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bri325228-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
50.800 (2)	BRI 325228 UU		889	50.800 (2)	82.550 (3 1/4)	44.450 (1 3/4)	44.700	

F _w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 324028 B
	d _s Min.	d _s Max.	D _s Max.				
63.500 (2 1/2)	58	61	74.3	94 600	174 000	3 000	

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382739
Inside diameter	50.8 mm
Outside diameter	82.55 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE