


## Needle roller bearing BRI365628-UU-IKO - BRI365628-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/bri365628-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		$d$	$D$	$C$	$B$
<b>57.150</b> (2 1/4)	<b>BRI 365628 UU</b>		<b>980</b>	<b>57.150</b> (2 1/4)	<b>88.900</b> (3 1/2)	<b>44.450</b> (1 3/4)	<b>44.700</b>
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring	
	Min.	Max.				Min.	Max.
<b>69.850</b> (2 3/4)	<b>65</b>	<b>67</b>	<b>98 700</b>	<b>189 000</b>	<b>2 500</b>	<b>LRBZ 364428 B</b>	

Notes: (\*) Minimum allowable value of diameter dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382746
Inside diameter	57.15 mm
Outside diameter	88.9 mm
Thickness	44.45 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE