


Needle roller bearing GBR364828-U-IKO - GBR364828-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/gbr364828-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
57.150 (2 1/4)	GBR 364828 U		515	57.150 (2 1/4)	76.200 (3)	44.450 (1 3/4)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A Max.	r as max (°)	N	N	rpm		
69.2	1.5	87 500	161 000	1 400		

Notes: (*) Minimum allowable value of diameter dimension r
(°) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383101
Inside diameter	57.15 mm
Outside diameter	76.2 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE