


Needle roller bearing GBR1264120-U-IKO - GBR1264120-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/gbri264120-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
41.275 (1 1/2)	GBR1264120 U		425	41.275 (1 1/2)	65.088 (2 3/8)	31.750 (1 1/4)

B	F _w	Standard mounting dimensions mm			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min.	Max.	r _{as max} ⁽¹⁾				
32.000	50.800 (2)	48	49	59.2	63 100	130 000	1 600	LRBZ 263220

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383491
Inside diameter	41.275 mm
Outside diameter	65.088 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE