


Needle roller bearing GBR1608432-U-IKO - GBR1608432-U-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/gbr1608432-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
95.250 (3 7/8)	GBR1608432 U		2 260	95.250 ± 0.010	133.350 ± 0.010	50.800 ± 0.010			
		Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	Assembled inner ring		
B	F _w	Min.	Max.	r _{as max} ⁽¹⁾	N	N	rpm		
51.050	107.950 ± 0.010	103	105	125.3	1.5	186 000	419 000	750	LRBZ 606832

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383668
Inside diameter	95.25 mm
Outside diameter	133.35 mm
Thickness	50.8 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE