

## Needle roller bearing NAFW304526-IKO - NAW304526-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/naw304526-iko>

**IKO**  
**NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE**  
With Inner Ring

Shaft dia. mm	Identification number	Mess (Ref.)	Boundary dimensions mm					Standard mounting dimensions mm				
		g	d	D	C	$r_s^{(1)}$	$F_w$	$d_a$	$D_s$	$d_s$	$D_d$	
<b>30</b>	<b>NAFW 304526</b>	155	30	45	26	0.3	35	39.5	43	32	34	35.6
Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(2)</sup>	Assembled roller ring									
N	N	rpm	LRT 303526									
26 600	51 500	14 000										

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952384597
Inside diameter	30 mm
Outside diameter	45 mm
Thickness	26 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE