

Needle roller bearing TRU405930-IKO - TRU405930-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/tru405930-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings

NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ r _{s min}	J	E _w
40	—	—	265	40	59	30	0.6	45	52.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾							
N	N	rpm							
34 700	62 500	8 500							

Note(1) Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: 1. This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952385365
Inside diameter	40 mm
Inside diameter	1.575" inch
Outside diameter	59 mm
Outside diameter	2.323" inch
Thickness	30 mm
Thickness	1.181" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE