

## Needle roller bearing TRU456430-IKO - TRU456430-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/tru456430-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings  
Full Complement Roller Bearings

NAl49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> F <sub>s</sub> min	J	E <sub>w</sub>
45	—	TRU 456430	295	45	64	30	0.6	50.5	58.5
Basic dynamic load rating C			Basic static load rating C <sub>0</sub>			Allowable rotational speed <sup>(2)</sup>			
N			N			rpm			
32 600			59 700			8 000			

Note<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
 Note<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952385396
Inside diameter	45 mm
Outside diameter	64 mm
Thickness	30 mm
Weight	320 g
Packaging	-
Standard	-

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE