

Needle roller bearing TRU608945-IKO - TRU608945-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/tru608945-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings

NAU49 TRU

| Shaft dia. mm | Identification number | | Mass (Ref.) g | Boundary dimensions mm | | | | | |
|-----------------------------|---|---|---------------|------------------------|----|----|-------------------------------------|------|----------------|
| | Full complement type | Caged type | | d | D | C | r ⁽¹⁾ r _{s min} | J | E _w |
| 60 | --- | TRU 608945 | 880 | 60 | 89 | 45 | 1 | 69.5 | 81.5 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ | | | | | | | |
| N | N | rpm | | | | | | | |
| 88 100 | 152 000 | 6 000 | | | | | | | |

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
 Note⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952385495 |
| Inside diameter | 60 mm |
| Inside diameter | 2.362" inch |
| Outside diameter | 89 mm |
| Outside diameter | 3.504" inch |
| Thickness | 45 mm |
| Thickness | 1.772" inch |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE