


Needle roller bearing NAU4922-IKO - NAU4922-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/nau4922-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings



NAU49 TRU

| Shaft dia. mm | Identification number | | Mass (Ref.) g | Boundary dimensions mm | | | | | |
|-----------------------------|-----------------------------------------|-------------------------------------------|---------------|------------------------|-----|----|-------------------------------------|-----|----------------|
| | Full complement type | Caged type | | d | D | C | r ⁽¹⁾ r _s min | J | E _w |
| 110 | — | NAU 4922 | 1 930 | 110 | 150 | 40 | 1.5 | 123 | 138.5 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ | | | | | | | |
| N | N | rpm | | | | | | | |
| 113 000 | 200 000 | 3 500 | | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952385730 |
| Inside diameter | 110 mm |
| Outside diameter | 150 mm |
| Thickness | 40 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE