

Needle roller bearing TRU284530-IKO - TRU284530-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/tru284530-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings

NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ r _{s min}	J	E _w
28	---	TRU 284530	173	28	45	30	0.3	31.5	39.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾							
N	N	rpm							
28 700	43 800	12 000							

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
 Note⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386058
Inside diameter	28 mm
Outside diameter	45 mm
Thickness	30 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE