


## Needle roller bearing NAU4909-UU-IKO - NAU4909-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/nau4909-uu-iko>

**IKO**  
**ROLLER BEARINGS**

Caged Roller Bearings **[With Seal]**  
Full Complement Roller Bearings **[With Seal]**



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r <sup>(1)</sup> min	J
45	---	NAU 4909UU		260	45	68	22	0.6	51
E <sub>w</sub>	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed n <sub>g</sub> rpm						
	N	N	3 500						

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
(\*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAU and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386164
Inside diameter	45 mm
Outside diameter	68 mm
Thickness	22 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE