

Needle roller bearing TRU456430-UU-IKO - TRU456430-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/tru456430-uu-iko>

IKO

ROLLER BEARINGS

Caged Roller Bearings **[With Seal]**

Full Complement Roller Bearings **[With Seal]**

NAU49-UU
TRU-UU

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type			d	D	C	r _{min} (*)	J	
45	---	---		TRU 456430UU	295	45	64	30	0.6	50.5
<i>E_w</i>	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _{gr}							
61	N 36 400	N 54 700	2 500							

Notes: (*) Minimum allowable value of chamfer dimension r
 (*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and NLU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386171
Inside diameter	45 mm
Inside diameter	1.772" inch
Outside diameter	64 mm
Outside diameter	2.52" inch
Thickness	30 mm
Thickness	1.181" inch
Weight	300 g
Packaging	1
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE