

## Needle roller bearing NAG4924-UU-IKO - NAG4924-UU-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/nag4924-uu-iko>

**IKO**

**ROLLER BEARINGS**

Caged Roller Bearings **[With Seal]**

Full Complement Roller Bearings **[With Seal]**

NAG49-UU

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r <sup>(1)</sup> min	J
120	<b>NAG 4924UU</b>	—		2 780	120	165	45	1.5	136
<i>E<sub>w</sub></i>	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup> rpm						
153.5	N 208 000	N 431 000	1 000						

Notes: (1) Minimum allowable value of chamfer dimension r.  
 (2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386669
Inside diameter	120 mm
Inside diameter	4.724" inch
Outside diameter	165 mm
Outside diameter	6.496" inch
Thickness	45 mm
Thickness	1.772" inch
Weight	2921 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE