


## Needle roller bearing NAS5034-UU-NR-IKO - NAS5034-UU-NR-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/nas5034-uu-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
170	NAS 5034UU	NR	22.5	170	260	270	122	121	99	11

f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm
4	3.5	1.5	204.5	857 000	1 730 000	600

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
(<sup>2</sup>) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952387109
Inside diameter	170 mm
Outside diameter	260 mm
Thickness	122 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE