

Needle roller bearing NBXI1425Z-IKO - NBXI1425Z-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/nbxi1425z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring

Shaft dia. mm	Identification number						d	D	D ₁		
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover					
14	---	---	---	---	---	---	NBXI 1425Z	72.5	14	26	30

Boundary dimensions mm				Bore diameter mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring						
D ₂	L	B	H			Radial	Radial			Axial					
31	25	17	9	8	0.3	0.3	17	28	16	12 900	11 400	16 300	28 600	13 000	LRT 141717

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390758
Inside diameter	14 mm
Outside diameter	26 mm
Thickness	25 mm
Weight	50 g
Packaging	-
Standard	-

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE