


## Needle roller bearing NAXI3030Z-IKO - NAXI3030Z-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/naxi3030z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring



Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
30		<b>NAXI 3030Z</b>	215	—	—	—	30	47	52

Boundary dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring							
D <sub>2</sub>	L	B	H		Radial	Axial			Radial	Axial					
53	30	20	12	9	0.6	0.3	35	45	34	26 900	21 200	46 200	37 600	6 000	LRT 303520

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390888
Inside diameter	30 mm
Outside diameter	47 mm
Thickness	30 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE