

Needle roller bearing NAXI3532Z-IKO - NAXI3532Z-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/naxi3532z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
35		NAXI 3532Z	273	—	—	—	35	52	60

Boundary dimensions mm			r ⁽¹⁾	r _{max}	r _{min}	d ₁	d ₂	d ₃	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 354020						
D ₂	L	H							Radial	Axial	Radial	Axial								
61	32	20	13	10	0.6	0.3	40	52	39	29	400	26	900	54	100	50	000	5	500	

Notes⁽³⁾
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390932
Inside diameter	35 mm
Outside diameter	52 mm
Thickness	32 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE