


Needle roller bearing NAXI4032Z-IKO - NAXI4032Z-IKO

<https://www.123bearing.com/bearing-housing/needle-roller-bearing/needle/naxi4032z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring



| Shaft dia. mm | Identification number | | | | | | d | D | D _i |
|------------------|-----------------------|-----------------|------------------|------------------|-----------------|------------------|----|----|----------------|
| | Mass (Ref.) g | With dust cover | Mass (Ref.) g | Mass (Ref.) g | With dust cover | Mass (Ref.) g | | | |
| 40 | NAXI 4032Z 324 | | | | | | 40 | 58 | 65 |

| Boundary dimensions mm | | | | Basic dynamic load rating C | Basic static load rating C ₀ | | Allowable rotational speed ⁽¹⁾ rpm | Assembled inner ring LRT 404520 | |
|---------------------------|----|----|----|--------------------------------|--|--------|--|------------------------------------|--------|
| D ₂ | L | B | H | | Radial | Axial | | | Radial |
| 66.5 | 32 | 20 | 14 | 9 | 31 000 | 27 900 | 60 200 | 55 100 | 5 000 |

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952390970 |
| Inside diameter | 40 mm |
| Outside diameter | 58 mm |
| Thickness | 32 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE