


GE Rod end
SB8513574-IKO - SB8513574-IKO

<https://www.123bearing.com/bearing-housing/rod-end/ge/sb8513574-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree
	SB	SB 8513574		d	D	B	C	d _k	r ₁ mm ⁽¹⁾	
85		SB 8513574	4.29	85	135	74	63	125	0.6	6
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s						
d _s	D _s									
Min.	Max. ⁽²⁾	Min.	N	N	N					
89.5	100.5	130.5	116	772 000	4 630 000					

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391472
Inside diameter	85 mm
Inside diameter	3.346" inch
Outside diameter	135 mm
Outside diameter	5.315" inch
Thickness	74 mm
Thickness	2.913" inch
Type	GE
Weight	4290 g
Lubrication	without
Dynamic load	772 kN
Static load	4630 kN
Packaging	1
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE