


GE Rod end SB150A-IKO - SB150A-IKO

<https://www.123bearing.com/bearing-housing/rod-end/ge/sb150a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree α	
			d	D	B	C	d_k ⁽¹⁾ r_s mm		
150	SB 150A	17.0	150	220	120	105	205	1	5
Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N						
d_s Min.	Max. ⁽²⁾		D_s Min.						
155.5	166	214.5	189	2 110 000	12 700 000				

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391625
Inside diameter	150 mm
Outside diameter	220 mm
Thickness	120 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE