

## GE Rod end GE240ES-IKO - GE240ES-IKO

<https://www.123bearing.com/bearing-housing/rod-end/ge/ge240es-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d <sub>s</sub>	r <sub>1</sub> <sup>(1)</sup> r <sub>1s</sub> min	r <sub>2</sub> <sup>(1)</sup> r <sub>2s</sub> min	α	α <sub>1</sub>
<b>240</b>	<b>GE 240ES</b>		<b>40,4</b>	<b>240</b>	<b>340</b>	<b>140</b>	<b>100</b>	<b>300</b>	<b>1,1</b>	<b>1,1</b>	<b>8</b>	<b>6</b>
Mounting dimensions mm		Dynamic load capacity C <sub>d</sub>		Static load capacity C <sub>s</sub>								
d <sub>s</sub>		D <sub>s</sub>		N		N						
Min.	Max. <sup>(2)</sup>	Max.	Min.									
<b>247</b>	<b>265</b>	<b>333</b>	<b>296</b>	<b>2 940 000</b>		<b>17 700 000</b>						

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392110
Inside diameter	240 mm
Outside diameter	340 mm
Thickness	140 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE