


## GE Rod end GE90GS-2RS-IKO - GE90GS-2RS-IKO

<https://www.123bearing.com/bearing-housing/rod-end/ge/ge90gs-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$
<b>90</b>	<b>GE 90GS-2RS</b>		5.41	90	150	85	55	130	1	1	15	14
Mounting dimensions mm		Dynamic load capacity $C_d$		Static load capacity $C_s$								
$d_s$		$D_s$		N		N						
Min.	Max.(2)	Max.	Min.									
95.5	98	144.5	127	701 000		4 210 000						

Notes(1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392486
Inside diameter	90 mm
Outside diameter	150 mm
Thickness	85 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE