


GE Rod end GE140GS-IKO - GE140GS-IKO

<https://www.123bearing.com/bearing-housing/rod-end/ge/ge140gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | | Permissible tilting angle degree | | |
|---------------------------|-----------------------|-----------------------------------|----------------------|----------------------------------|------------|------------|-----------|------------|-----------|-----------|--|------------|--|
| | Without seals | With seals | | d | D | B | C | d_s | r_1 (1) | r_2 (1) | α | α_1 | |
| 140 | GE 140GS | | 19.2 | 140 | 230 | 130 | 80 | 200 | 1 | 1 | 16 | 15 | |
| Mounting dimensions mm | | Dynamic load capacity C_d | | Static load capacity C_s | | | | | | | | | |
| d_s | D_s | | | | | | | | | | | | |
| Min. | Max.(2) | Max. | Min. | N | | N | | | | | | | |
| 145.5 | 152 | 224.5 | 195 | 1 570 000 | | 9 410 000 | | | | | | | |

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952392554 |
| Inside diameter | 140 mm |
| Outside diameter | 230 mm |
| Thickness | 130 mm |
| Type | GE |
| Lubrication | without |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE