


GE Rod end GE220GS-2RS-IKO - GE220GS-2RS-IKO

<https://www.123bearing.com/bearing-housing/rod-end/ge/ge220gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
220	GE 220GS-2RS		51.3	220	340	175	100	300	1.1	1.1	16	14
Mounting dimensions mm			Dynamic load capacity C_d N	Static load capacity C_s N								
d_s	D_s	D_s										
Min.	Max.(2)	Max.	Min.									
227	243.5	333	296	2 940 000	17 700 000							

Notes(1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392646
Inside diameter	220 mm
Outside diameter	340 mm
Thickness	175 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE