

## GE Rod end GE260GS-IKO - GE260GS-IKO

<https://www.123bearing.com/bearing-housing/rod-end/ge/ge260gs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d <sub>s</sub>	r <sub>1</sub> (1)	r <sub>2</sub> (2)	α	α <sub>1</sub>
<b>260</b>	<b>GE 260GS</b>		81.8	260	400	205	120	350	1.1	1.1	15	14
Mounting dimensions mm		Dynamic load capacity C <sub>d</sub> N		Static load capacity C <sub>s</sub> N								
d <sub>s</sub>		D <sub>s</sub>										
Min.	Max.(?)	Max.	Min.									
267	283.5	393	345	4 120 000		24 700 000						

Notes (1) Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392677
Inside diameter	260 mm
Inside diameter	10.236" inch
Outside diameter	400 mm
Outside diameter	15.748" inch
Thickness	205 mm
Thickness	8.071" inch
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE