

GE Rod end SBB80-2RS-IKO - SBB80-2RS-IKO

<https://www.123bearing.com/bearing-housing/rod-end/ge/sbb80-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
127.000 (5)		SBB 80-2RS	13.5	127.000 (5)	196.850 (7 7/8)	111.12 (4.375)	95.25 (3.750)
Radial internal clearance mm	Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N			
	d _k Min./Max.	d ₁ r ₁ max. r ₂ max.		r ₁ r ₂	C _d	C _s	
183 (7.205)	0.13 / 0.23	144.9	0.8	1.1	1 710 000	10 300 000	

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952393094
Inside diameter	127 mm
Outside diameter	196.85 mm
Thickness	111.12 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE