

## Tapered roller bearing 33225-33462-JTEKT - 33225-33462-KOYO

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/33225-33462-koyo>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
57.150	117.475	30.162	30.162	22.812	3.6	3.2	118	179	3 200	4 200

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to Mass (kg))		
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
33225	33462	27.8	74.0	68.0	104.0	112.0	3.6	3.2	0.44	1.38	0.76	1.13	0.442

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428208
Inside diameter	57.15 mm
Outside diameter	117.475 mm
Thickness	30.162 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE