


## Tapered roller bearing 29688-29620-JTEKT - 29688-29620-KOYO

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/29688-29620-koyo>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)										Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.			
73.817	112.712	25.400	25.400	19.050	1.6	3.2	97.0	155	3 200	4 300			

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
29688	29620	26.2	83.0	81.0	101.0	109.0	1.6	3.2	0.49	1.23	0.68	0.588	0.270

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429007
Inside diameter	73.817 mm
Inside diameter	2 29/32" inch
Outside diameter	112.712 mm
Outside diameter	4 7/16" inch
Thickness	25.4 mm
Thickness	1" inch
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE