

## Tapered roller bearing 594A-592XE-JTEKT - 594A-592XE-KOYO

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/594a-592xe-koyo>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		
d	D	T	B	C	d <sub>a</sub>	d <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
95.250	147.638	35.717	36.322	26.192	5.2	0.8			183	287	2 400	3 300

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
594A	592XE	33.4	113.0	104.0	135.0	142.0	5.2	0.8	0.44	1.36	0.75	1.45	0.620

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429823
Inside diameter	95.25 mm
Outside diameter	147.638 mm
Thickness	35.717 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE