


Cam follower CF12-V-IKO - CF12-V-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf12-v-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm	Identification number								CF-V					
	Shield type				Sealed type				Mass (Ref.)					
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring		g	D	C	d ₁		
12	CF 12		V						97	30	14	12		
Boundary dimensions mm														
G	G ₁	B _{max}	B _{1max}	B ₂	B ₃	C ₁	g ₁	g ₂	f ⁽¹⁾ Min. mm	Mounting diameter f _{min} mm	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M12×1.5	13	15.2	40.2	25	6	0.6	6	3	0.6	21	21.9	13 500	19 700	13 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952440408
Inside diameter	12 mm
Outside diameter	30 mm
Thickness	14 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE