


Cam follower CF8-R-IKO - CF8-R-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf8-r-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
8	CF	8	R		28.5	19	11	8	M 8×1.25

Boundary dimensions mm													
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max (°)	f Min. mm	Maximum ignoring torque N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
10	12.2max	32.2max	20	—	0.6	*4	—	0.3	13	6.5	4 250	4 740	4 620

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952440996
Inside diameter	8 mm
Outside diameter	19 mm
Thickness	11 mm
Weight	40 g
Packaging	-
Standard	-

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE