


Cam follower CF10-RM-IKO - CF10-RM-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf10-rm-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
10	CF 10 RM				45	22	12	10	M10×1

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N·m	Ball diameter load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _{max} (°)	r _{min}					
12	13.2max	36.2max	23	—	0.6	*4	—	0.3	16	14.7	5 430	6 890	6 890	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441115
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	12 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE