


Cam follower CF12-R-IKO - CF12-R-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf12-r-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
12	CF 12	R			95	30	14	12	M12×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N·m	Ball diameter load rating C	Ball static load rating C ₀	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max	(°)					
13	15.2max	40.2max	25	6	0.6	6	3	0.6	21	21.9	7 910	9 790	9 790	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441245
Inside diameter	12 mm
Inside diameter	0.472" inch
Outside diameter	30 mm
Outside diameter	1.181" inch
Thickness	14 mm
Thickness	0.551" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE