


Cam follower CF20-1-UU-IKO - CF20-1-UU-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf20-1-uu-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

| Stud dia. mm | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G |
|-----------------|----------------------------|--------------------------------|----------------------------|--------------------------------|---------------------|----|----|----------------|---------|
| | Shield type | | Sealed type | | | | | | |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | | |
| 20 | | | | CF 20-1 UU | 385 | 47 | 24 | 20 | M20×1.5 |

| Boundary dimensions mm | | | | | | | | | | | | | |
|------------------------|---------|----------------|----------------|----------------|----------------|----------------|----------------|---------------------------|--|--|---------------------------------------|---|--|
| G ₁ | B | B ₁ | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | r _s max (°) | Mounting dimension f Min. mm | Maximum tightening torque N·m | Ball dynamic load rating C N | Ball static load rating C ₀ N | Maximum allowable static load N |
| 21 | 25.6max | 66.1max | 40.5 | 9 | 0.8 | 8 | 4 | 1 | 34 | 119 | 20 700 | 34 600 | 34 600 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952441474 |
| Inside diameter | 20 mm |
| Outside diameter | 47 mm |
| Thickness | 20 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE