

Cam follower CF30-2-UUR-IKO - CF30-2-UUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf30-2-uur-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



| Stud dia. mm | Identification number | | | | Mass (Ref.) g | D | C | d ₁ | G |
|-----------------|----------------------------|--------------------------------|----------------------------|--------------------------------|---------------------|----|----|----------------|---------|
| | Shield type | | Sealed type | | | | | | |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | | |
| 30 | CF 30-2 UUR | | | | 2 220 | 90 | 35 | 30 | M30×1.5 |

| Boundary dimensions mm | | | | | | | | | | Mounting torque N·m | Ball dynamic load rating C | Ball static load rating C ₀ | Maximum allowable static load N | | |
|------------------------|----|----------------|----------------|----------------|----------------|----------------|----------------|---------------------------|-----------------|---------------------------|----------------------------------|--|--|--------|--------|
| G ₁ | B | B ₁ | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | r _s max (°) | f Min. mm | | | | | | |
| 32 | 37 | max | 100 | max | 63 | 15 | 1 | 8 | 4 | 1 | 49 | 438 | 45 400 | 85 100 | 85 100 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952441665 |
| Inside diameter | 30 mm |
| Outside diameter | 90 mm |
| Thickness | 35 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE