


Cam follower CF10-VBM-IKO - CF10-VBM-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf10-vbm-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Hexagon Hole



Stud dia. mm	Identification number								Mass (Ref.)				
	Shield type				Sealed type				g	D	C	d ₁	
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring						
10	CF 10		VBM						46	22	12	10	

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	G ₁	B max	B ₁ max	B ₂	B ₃	C ₁	g ₁	g ₂	H K/min						
M10×1	12	13.2	36.2	23	—	0.6	—	—	4	0.3	16	14.7	9 570	14 500	8 650

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441870
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	12 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE