


Cam follower CF10-1-VBUUM-IKO - CF10-1-VBUUM-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf10-1-vbuum-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Hexagon Hole



CF-VBUU

Stud dia. mm	Identification number								Mass (Ref.)						
	Shield type				Sealed type				g	D	C	d ₁			
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring								
10					CF 10-1 VBUUM				61	26	12	10			
Boundary dimensions mm															
G	G ₁	B _{max}	B _{1 max}	B ₂	B ₃	C ₁	g ₁	B ₂	H ^(*)	f ^(*) Min. mm	Mounting dimension Max. mm	Max. dynamic load N-m	Basic dynamic load rating C	Basic static load rating C ₀	Maximum allowable static load N
M10×1	12	13.2	36.2	23	—	0.6	—	—	4	0.3	16	14.7	9 570	14 500	8 650

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441979
Inside diameter	10 mm
Outside diameter	26 mm
Thickness	12 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE