


## Cam follower CF12-1-VB-IKO - CF12-1-VB-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf12-1-vb-iko>



### CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Hexagon Hole



CF-VB

| Stud dia.<br>mm | Identification number   |                             |                         |                             |                         |                             |                         |                             | Mass (Ref.) |    |    |                |  |
|-----------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|--|
|                 | Shield type             |                             |                         |                             | Sealed type             |                             |                         |                             | g           | D  | C  | d <sub>1</sub> |  |
|                 | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring |             |    |    |                |  |
| 12              | CF 12-1 VB              |                             |                         |                             |                         |                             |                         |                             | 107         | 32 | 14 | 12             |  |

| Boundary dimensions mm |                |                  |                   |                |                |                |                |                |   | Mounting dimension     | Maximum tightening torque | Basic dynamic load rating | Basic static load rating | Maximum allowable static load |        |
|------------------------|----------------|------------------|-------------------|----------------|----------------|----------------|----------------|----------------|---|------------------------|---------------------------|---------------------------|--------------------------|-------------------------------|--------|
| G                      | G <sub>1</sub> | B <sub>max</sub> | B <sub>1max</sub> | B <sub>2</sub> | B <sub>3</sub> | C <sub>1</sub> | g <sub>1</sub> | B <sub>2</sub> | H | f <sup>(*)</sup><br>mm | N·m                       | C                         | C <sub>0</sub>           | N                             |        |
| M12×1.5                | 13             | 15.2             | 40.2              | 25             | 6              | 0.6            | 6              | 3              | 6 | 0.6                    | 21                        | 21.9                      | 13 500                   | 19 700                        | 13 200 |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | IKO           |
| N° Ean13         | 3663952442037 |
| Inside diameter  | 12 mm         |
| Outside diameter | 32 mm         |
| Thickness        | 14 mm         |
| Packaging        | 1             |

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE