


## Cam follower CF8-BRM-IKO - CF8-BRM-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf8-brm-iko>



### CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Hexagon Hole



Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G
	Shield type		Sealed type						
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring					
8	CF	8	BRM		28.5	19	11	8	M 8×1

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum spinning torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
G <sub>1</sub>	B	B <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	H	r <sub>s</sub> μm					
10	12.2max	32.2max	20	—	0.6	—	—	4	0.3	13	7.1	4 250	4 740	4 620

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952442617
Inside diameter	8 mm
Outside diameter	19 mm
Thickness	11 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE