


Cam follower CF12-B-IKO - CF12-B-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cf12-b-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Hexagon Hole



CF-B

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring					
12		CF 12 B			95	30	14	12	M12×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum spinning torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	H	r _s max					
13	15.2max	40.2max	25	6	0.6	6	3	6	0.6	21	21.9	7 910	9 790	9 790

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952442839
Inside diameter	12 mm
Outside diameter	30 mm
Thickness	14 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE