


## Cam follower CFES10-1-BUUR-IKO - CFES10-1-BUUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfes10-1-buur-iko>



### CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers With Cage/With Hexagon Hole



CFES-BUUR

| Stud dia.<br>mm        | Identification number   |      |                             |                |                |                         |                |                             |   |                  | Mass (Ref.)       |                                       |                                      |  |  |  |
|------------------------|-------------------------|------|-----------------------------|----------------|----------------|-------------------------|----------------|-----------------------------|---|------------------|-------------------|---------------------------------------|--------------------------------------|--|--|--|
|                        | Shield type             |      |                             |                |                | Sealed type             |                |                             |   |                  | g                 | D                                     | C                                    | d <sub>1</sub>                         |  |  |
|                        | With crowned outer ring |      | With cylindrical outer ring |                |                | With crowned outer ring |                | With cylindrical outer ring |   |                  |                   |                                       |                                      |  |  |  |
| 10                     | <b>CFES 10-1 BUUR</b>   |      |                             |                |                |                         |                |                             |   |                  | 60                | 26                                    | 12                                   | 10                                     |  |  |
| Boundary dimensions mm |                         |      |                             |                |                |                         |                |                             |   |                  |                   |                                       |                                      |  |  |  |
| G                      | G <sub>1</sub>          | B    | B <sub>1</sub>              | B <sub>2</sub> | B <sub>3</sub> | C <sub>1</sub>          | g <sub>1</sub> | g <sub>2</sub>              | H | H <sub>max</sub> | Eccentricity<br>E | Mounting dimension<br>f<br>Min.<br>mm | Maximum<br>spinning<br>torque<br>N·m | Basic dynamic<br>load rating<br>C<br>N | Basic static<br>load rating<br>C <sub>0</sub><br>N | Maximum<br>allowable<br>static load<br>N |
| M10×1.25               | 12                      | 13.2 | 36.2                        | 23             | —              | 0.6                     | —              | —                           | 4 | 0.3              | 0.3               | 16                                    | 13.8                                 | 5 430                                  | 6 890  | 6 890                                    |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | IKO           |
| N° Ean13         | 3663952443508 |
| Inside diameter  | 10 mm         |
| Outside diameter | 26 mm         |
| Thickness        | 12 mm         |
| Packaging        | 1             |

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE