


Cam follower CFES12-B-IKO - CFES12-B-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfes12-b-iko>



CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers | With Cage/With Hexagon Hole



CFES-B

Stud dia. mm	Identification number								Mass (Ref.) g	D	C	d ₁				
	Shield type				Sealed type											
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring									
12	CFES 12 B								95	30	14	12				
Boundary dimensions mm																
G	G ₁	B max	B ₁ max	B ₂	B ₃	C ₁	g ₁	g ₂	H max	ε ^(°)	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M12×1.5	13	15.2	40.2	25	6	0.6	6	3	6	0.6	0.4	21	21.9	7 910	9 790	9 790

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952443546
Inside diameter	12 mm
Outside diameter	30 mm
Thickness	14 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE