

Cam follower CFE20-B-IKO - CFE20-B-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe20-b-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Hexagon Hole



CFE-B

Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
27	CFE 20 B						500	52	24	27

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	B ₃	B _{max}	B _{1 max}	B ₂	C ₁	G ₁	H	(1) Fit	e						
M20×1.5	19.5	25.6	66.1	40.5	0.8	8	21	8	1	0.8	34	119	20 700	34 600	34 600

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459527
Inside diameter	27 mm
Outside diameter	52 mm
Thickness	24 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE