


Cam follower CFE8-IKO - CFE8-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe8-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d ₂
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
11	CFE 8						32	19	11	11

Boundary dimensions mm										Essentiality g	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₁ max	B ₂	C ₁	g ₁	G ₁	(1) f _{max}	e						
M 8×1.25	9.5	12.2	32.2	20	0.6	*4	10.5	0.3	0.4	13	6.5	4 250	4 740	4 620	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459794
Inside diameter	11 mm
Inside diameter	0.433" inch
Outside diameter	19 mm
Outside diameter	0.748" inch
Thickness	11 mm
Thickness	0.433" inch
Weight	32 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE