


Cam follower CFE10-UUR-IKO - CFE10-UUR-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe10-uur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		\emptyset	D	C	d_2
13	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	49.5	22	12	13
CFE 10 UUR								

Boundary dimensions mm														
G	B_3	B max	B_1 max	B_2	C_1	G_1	(°) r_{max}	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N	Maximum allowable static load N		
M10×1.25	10.5	13.2	36.2	23	0.6	*4	12.5	0.3	0.4	16	13.8	5 430	6 890	6 890

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459824
Inside diameter	13 mm
Inside diameter	0.512" inch
Outside diameter	22 mm
Outside diameter	0.866" inch
Thickness	12 mm
Thickness	0.472" inch
Weight	49.5 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE