


## Cam follower CFE12-IKO - CFE12-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe12-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d <sub>2</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
16	CFE 12						105	30	14	16

Boundary dimensions mm										Essentiality	Mounting dimension f Min, mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
G	B <sub>3</sub>	B max	B <sub>1</sub> max	B <sub>2</sub>	C <sub>1</sub>	G <sub>1</sub>	G <sub>1</sub> (1)	r <sub>max</sub>	e						
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21	21.9	7 910	9 790	9 790	

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459893
Inside diameter	16 mm
Outside diameter	30 mm
Thickness	14 mm
Weight	105 g
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE