


Cam follower CFE12-1-UU-IKO - CFE12-1-UU-IKO

<https://www.123bearing.com/bearing-housing/deep-groove-bearing/cam-follower/cfe12-1-uu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



| Outside diameter of eccentric collar mm | Identification number | | | | | | Mass (Ref.) | | | |
|---|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|--|-------------|----|----|----------------|
| | Shield type | | | Sealed type | | | Ø | D | C | d ₂ |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | CFE 12-1 UU | | | | | |
| 16 | | | | | | | 115 | 32 | 14 | 16 |

| Boundary dimensions mm | | | | | | | | | | Essentiality | Mounting dimension f Min, mm | Maximum tightening torque N-m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
|------------------------|----------------|-------|--------------------|----------------|----------------|----------------|----------------|---------|-----|--------------|------------------------------|-------------------------------|-------------------------------|---|---------------------------------|
| G | B ₃ | B max | B ₁ max | B ₂ | C ₁ | g ₁ | G ₁ | (°) max | e | | | | | | |
| M 8×1.25 | 9.5 | 12.2 | 32.2 | 20 | 0.6 | *4 | 10.5 | 0.3 | 0.4 | 13 | 6.5 | 4 250 | 4 740 | 4 620 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060459954 |
| Inside diameter | 16 mm |
| Outside diameter | 32 mm |
| Thickness | 14 mm |
| Weight | 115 g |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE